

ICS 59.080.30; 59.080.80

ČSN
EN IEC 63203-201-2
OPRAVA 1
35 9350

Březen 2024

ČESKÁ TECHNICKÁ NORMA

**Nositelná elektronická zařízení a technologie –
Část 201-2: Elektronické textilie – Metody měření základních
vlastností vodivých textilií a izolačních materiálů**



EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

**EN IEC 63203-201-
2:2022/AC:2023-12**

December 2023

ICS 59.080.80; 59.080.30

English Version

**Wearable electronic devices and technologies - Part 201-2:
Electronic textile - Measurement methods for basic properties of
conductive fabrics and insulation materials
(IEC 63203-201-2:2022/COR1:2023)**

Technologies et dispositifs électroniques prêts-à-porter -
Partie 201-2: Textile électronique - Méthodes de mesure
des propriétés fondamentales des étoffes conductrices et
des matériaux isolants
(IEC 63203-201-2:2022/COR1:2023)

Tragbare elektronische Geräte und Technologien - Teil 201-
2: Elektronische Textilien - Messverfahren für die
grundlegenden Eigenschaften von leitfähigen Textilien und
Isolationswerkstoffen
(IEC 63203-201-2:2022/COR1:2023)

This corrigendum becomes effective on 8 December 2023 for incorporation in the English language version of the EN.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Endorsement notice

The text of the corrigendum IEC 63203-201-2:2022/COR1:2023 was approved by CENELEC as EN IEC 63203-201-2:2022/AC:2023-12 without any modification.

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 63203-201-2
Edition 1.0 2022-04

IEC 63203-201-2
Édition 1.0 2022-04

**WEARABLE ELECTRONIC DEVICES
AND TECHNOLOGIES –**

**TECHNOLOGIES ET DISPOSITIFS
ÉLECTRONIQUES PRÊTS-À-PORTER –**

**Part 201-2: Electronic textile – Measurement
methods for basic properties of conductive
fabrics and insulation materials**

**Partie 201-2: Textile électronique – Méthodes de
mesure des propriétés fondamentales des
étoffes conductrices et des matériaux isolants**

CORRIGENDUM 1

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

Figure 2, Figure 3, Figure 4, and Figure 5

Replace the existing keys of the above figures (excluding values or symbols):

- 1 stretchable substrate
- 2 stretchable conductor
- 3 stretchable insulator

with the following new key:

- 1 non-conductive fabric as substrate
- 2 conductive fabric
- 3 cover insulation material

6.1.3.2.1 Procedure

Replace the existing list item a) with the following new list item a):

- a) Test specimens should be prepared as shown in Figure 2. The test specimens consist of a substrate, a rectangular **conductive fabric** of 70 mm × 210 mm, and a cover insulation layer of 70 mm × 70 mm.

The test specimen substrate shall have a margin of at least 5 mm on each side of the edges of the conductor. Dimensional errors of ±1 mm are allowed for **conductive fabric** and cover insulation layer.

6.1.3.3.1 Procedure

Replace the existing third paragraph with the following new third paragraph:

Place a 25 mm diameter electrode on the test specimen insulator layer at a pressure of 1 kg/cm² (the area of 25 mm diameter circle is 4,9 cm²; that is, the weight of the electrode is 4,9 kg). The electrode is placed at least 10 mm away from the edge of the insulator layer. Measure the breakdown voltage between electrode and **conductive fabric** with an electric breakdown tester conforming to IEC 60243-1:2013. Apply AC voltage, gradually increase the voltage and read the voltage value at which the dielectric breakdown occurs. At least five points are measured and the maximum, minimum and average values and breakdown mode of each test are recorded.

6.1.3.5.1 Procedure

Replace the existing second paragraph with the following new second paragraph:

Hold the test specimen on a horizontal insulation table with the substrate side facing upward. Place a 25 mm diameter electrode on the test specimen insulator layer at a pressure of 1 kg/cm² (the area of 25 mm diameter is 4,9 cm²; that is, the weight of the electrode is 4,9 kg). The electrode is placed at least 15 mm away from the edge of the substrate. Measure the breakdown voltage between electrode and **conductive fabric** with an electric breakdown tester conforming to IEC 60243-1:2013. Apply AC voltage, gradually increase the voltage and read the voltage value at which the dielectric breakdown occurs. At least five points are measured and the maximum, minimum and average values and breakdown mode of each test are recorded.

U p o z o r n ě n í : Oznámení o změnách, opravách a nově vydaných normách jsou uveřejňována ve Věstníku Úřadu pro technickou normalizaci, metrologii a státní zkušebnictví.

Vaše názory, podněty a připomínky týkající se technických norem a zájmu o možnou účast v procesech technické normalizace lze zaslat na e-mailovou adresu info@agentura-cas.cz.

ČSN EN IEC 63203-201-2 OPRAVA 1



518845

Vydala Česká agentura pro standardizaci na základě ustanovení § 5 odst. 2 zákona č. 22/1997 Sb.
Rok vydání 2024, 8 stran
Cenová skupina 998